



KEY FEATURES

- Intel® 12th Gen (Alder Lake-P) Core™ Processors
- 2 x 260-pin SO-DIMM up to 64GB DDR4 3200 MHz
- 5 x USB 3.2 Gen2, 1 x M.2 Key M, 1 x M.2 Key E (WiFi-6E), 1 x SATA3
- 2 x Intel 2.5 Gigabit LAN
- Supports Quad display, 1 x HDMI 2.0b, 3 x DP 1.4a (2 from Type C)
- TPM 2.0 onboard IC
- 19V/90W Power Adapter
- 110.0 x 117.5 x 47.85mm, Fanned Barebone

SPECIFICATIONS

Processor System

| | |
|---------|---|
| CPU | Intel® 12th Gen (Alder Lake-P) Core™ Processors NUC BOX-1260P (i7-1260P) NUC BOX-1240P (i5-1240P) NUC BOX-1220P (i3-1220P) |
| Chipset | MCP |
| BIOS | AMI SPI 256 Mbit |

Memory

| | |
|------------|----------------------------|
| Technology | Dual Channel DDR4 3200 MHz |
| Capacity | 64GB (32 GB per DIMM) |
| Socket | 2 x 260-pin SO-DIMM |

Graphics

| | |
|--------------|--|
| Controller | Intel® Iris® Xe Graphics for i7/i5 CPU Intel® UHD Graphics for i3/Celeron CPU |
| HDMI | HDMI 2.0b Max resolution up to 4096x2160@60Hz |
| DisplayPort | DisplayPort 1.4a, DP++ Max resolution up to 7680x4320@30Hz |
| MultiDisplay | Quad-Display (Included 2 outputs from Type-C) |

Expansion Slot

| | |
|-----------|---|
| M.2/ WLAN | 1 x Wi-Fi 6E 802.11ax (2.4Gbps) + BT 5.2 (M.2 Key E, 2230 PCIe x1, USB 2.0 for Wireless) |
|-----------|---|

Audio

| | |
|-----------|--|
| Interface | Realtek ALC233, High Definition Audio. |
|-----------|--|

Ethernet

| | |
|-------------------|--|
| Controller/ Speed | Intel® I225LM with 10/100/1000/2500 Mbps |
| Connector | 2 x RJ-45 |

Storage

| | |
|------|--|
| M.2 | 1 x M.2 (Key M, 2242/2260/2280) with PCIe Gen4 x4 for SSD *M.2 Key M 2280(Supported by bracket) |
| SATA | 1 x SATA3.0 (6.0 Gb/s) |

Front I/O

| | |
|-------|--|
| USB | 1 x USB 3.2 Gen2 (Type A) 2 x USB 3.2 Gen2 (Type-C, Supports DP1.4a display output) * USB4™ Compliance Test is pending for certification |
| Audio | 1 (headphone & microphone jack) |

Rear I/O

| | |
|-------------|---------------------------|
| HDMI | 1 x HDMI 2.0b |
| DisplayPort | 1 x DP1.4a |
| Ethernet | 2 x 2.5 Gigabit LAN |
| USB | 2 x USB 3.2 Gen2 (Type-A) |
| DC Jack | 1 |

Watchdog Timer

| | |
|-----------------|--|
| Output Interval | From Super I/O to drag RESETCON# 256 Segments, 0, 1, 2, ...255sec |
|-----------------|--|

Power Requirements

| | |
|-----------|---|
| Input PWR | 12V~19V DC-In Jack |
| Power On | AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready |

Environment

| | |
|--------------------|----------------|
| Operating Temp | 0°C ~ 40°C |
| Storage Temp | -40° C ~ 85° C |
| Operating Humidity | 5% ~ 90% |
| Storage Humidity | 5% ~ 90% |

Mechanical

| | |
|------------------------|--------------------------|
| Construction | Plastic with sheet metal |
| Mounting | VESA mounting |
| Dimensions (W x D x H) | 110.0 x 117.5 x 47.85mm |
| Weight | Net Weight:1.0Kg |

Others

| | |
|----------------|---|
| OS Support | Windows 10/11 |
| TPM | TPM 2.0 onboard IC |
| Certifications | CE, FCC Class A |
| Packing List | 1 x 19V/90W Power Adapter 1 x Screw Package 1 x VESA mounting bracket |