


# ICF

## 1ME series

### Drawing



### Specifications

Interface	PATA
Flash Type	MLC
Capacity	8GB~256GB
Max. Channels	2
Sequential R/W (MB/sec, max.)	110/110
Max. Power Consumption	0.76W(3.3V x 230mA)
Thermal Sensor	-
External DRAM Buffer	-
H/W Write Protect	Optional
ATA Security	√
S.M.A.R.T.	√
Dimension (WxLxH)	42.8X 36.4 X 3.3 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours

### Ordering Information

Operation Temp.	8GB	16GB	32GB	64GB	128GB	256GB
Standard Grade (0°C ~ +70°C)	DECFC-08GD53BC1SC	DECFC-16GD53BC1SC	DECFC-32GD53BC1DC	DECFC-64GD53BC1DC	DECFC-A28D53BC1DC	DECFC-B56D53BC1DC
Industrial Grade (-40°C ~ +85°C)	DECFC-08GD53BW1SC	DECFC-16GD53BW1SC	DECFC-32GD53BW1SC	DECFC-64GD53BW1DC	DECFC-A28D53BW1DC	DECFC-B56D53BW1DC