

GPU A+ Server AS -8125GS-TNHR



More details here

Key Applications

High Performance Computing, AI/Deep Learning Training, Industrial Automation, Retail, Climate and Weather Modeling,

Key Features

- Highest GPU communication using NVIDIA® NVLINK™ + NVIDIA® NVSwitch™; 8 NIC for GPU direct RDMA (1:1 GPU Ratio); High density 8U system with NVIDIA® HGX™ H100 8-GPU;
- 24 DIMM Slots; Up to 6TB DRAM; 4800 ECC DDR5 LRDIMM; RDIMM;;
- 8 PCIe Gen 5.0 X16 LP, and up to 4 PCIe Gen 5.0 X16 FHFL Slots;
- Flexible networking options;
- 2x 2.5" Hot-swap SATA drive bays; 1 M.2 NVMe for boot drive only; 12x 2.5" Hot-swap NVMe drive bays;
- 10 heavy duty fans with optimal fan speed control;
- 6x 3000W redundant Titanium level power supplies;



Form Factor	8U Rackmount Enclosure: 437 x 355.6 x 843.28mm (17.2" x 14" x 33.2") Package: 698 x 750 x 1300mm (27.5" x 29.5" x 51.2")
Processor	AMD EPYC™ 9004 Series Processors Dual Socket (Socket SP5) supported TDP up to 400W;
GPU	Supported GPU: HGX H100 8-GPU SXM5 Multi-GPU Board CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect GPU-GPU Interconnect: NVIDIA® NVLink™ with NVSwitch™
System Memory	24 DIMM slots Up to 6TB ECC LRDIMM, DDR5-4800MHz
Drive Bays	14x 2.5" hot-swap NVMe/SATA drive bays (12x 2.5" NVMe dedicated) 1 M.2 NVMe
Expansion Slots	8 PCIe 5.0 x16 LP slot(s) 2 PCIe 5.0 x16 FHFL slot(s)
On-Board Devices	Chipset: AMD SP5 Network Connectivity: 2x 10GbE BaseT with Intel® X550-AT2 (optional) IPMI: Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Input / Output	Video: 1 VGA port(s)

System Cooling	10 heavy duty fan(s)
Power Supply	6x 3000W (3+3) Redundant Power Supplies, Titanium Level Output Type: Backplanes (connector)
System BIOS	BIOS Type: AMI 32MB SPI Flash EEPROM
Management	SuperDoctor® 5; Watch Dog; NMI; SUM; KVM with dedicated LAN; SPM; Intel® Node Manager; SSM; IPMI 2.0; Redfish API; OOB Management Package (SFT-OOB-LIC)
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory 7 +1 Phase-switching voltage regulator FAN: Fans with tachometer monitoring Status monitor for speed control Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Height: 14" (355.6 mm) Width: 17.2" (437 mm) Depth: 33.2" (843.28 mm) Gross Weight: 225 lbs (102.1 kg) Net Weight: 166 lbs (75.3 kg) Packaging: 29.5" (H) x 27.5" (W) x 51.2" (D) Available Color: Black Front & Silver Body
Operating Environment	Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	Super H13DSG-O-CPU
Chassis	CSE-GP801TS