

# ACP-4320

## Quiet 4U Rackmount Chassis with Dual Hot-Swap SATA HDD Trays



### Features


- Supports either an ATX motherboard or a PICMG backplane with up to 15 slots
- Supports dual SATA hot-swap HDD trays
- LED indicators and alarm notification for system fault detection
- Low noise system fans
- Built-in Intelligent System Module enabling whole system fan control and remote manageability

### Quiet Specifications

CE FCC

		External	Internal
Driver Bay	5.25"	2	-
	3.5"	1 SATA Tray	-
	Hot Swap (SATA only)	2 (Compatible with both 3.5" or 2.5" devices, no convert bracket needed)	
Cooling	Fan	1(12 cm/82 CFM) + 1 (6cm / 28 CFM)	
	Air Filter	Yes	
	Smart Fan	System fan speed referring to chassis thermal sensor, or CPU temperature (Available with selected Advantech MBs/CPU cards)	
Front I/O Interface	USB 2.0	2	
Miscellaneous	LED Indicators	Power, HDD, temperature, fan, LAN1 and LAN2	
	Rear Panel	Backplane version: One 9-pin D-Sub opening Motherboard version: Five 9-pin D-Sub opening and one 25-pin D-sub opening	
Intelligent System Module Hardware Monitoring	CPU/System fan speed, CPU/system temperature (Only Advantech AIMB-78X, PCE-51XX/71XX mainboards can enable CPU fan speed and temperature monitoring function of Intelligent System Module)		
Environment	Temperature	Operating 0 ~ 40 °C (32 ~ 104 °F)	Non-Operating - 20 ~ 60 °C (-4 ~ 140 °F)
	Humidity	10 ~ 85% @ 40 °C , non-condensing	
	Vibration (5 ~ 500 Hz)	1 Grms	
Physical Characteristics	Dimension (W x H x D)	482 x 177 x 479 mm (19" x 7.0" x 18.9")	
	Weight	17.6 kg (38.7lb)	

### Front View




### Inside View

Easy-to-maintain system fan



## Dimensions



## Ordering Information

Number	Power supply	Power supply type	Wattage	80 plus grade	Switch type
<b>Backplane version</b>					
ACP-4320BP-00C	(NA, barebone)	NA	NA	NA	ATX
<b>Motherboard version</b>					
ACP-4320MB-00C	(NA, barebone)	NA	NA	NA	ATX
ACP-4320MB-50C	PS8-500ATX-BB	Single	500W	Bronze	ATX

## Packaging List

Part number	Description	Quantity
ACP-4320, Rev.C	ACP-4320 chassis	1
1750008561-01	12 cm system PWM fan	1
1700024778-11	fan cable for 12cm system fan	1
1750009289-01	6 cm PWM fan for hot-swap tray	1
1700030260-01	fan cable for 6 cm how-swap tray fan	1
98R2132000E	hot-swap tray	2
1990001298	plastic door filter	2
1990001299	Fan filter	2
<b>Content of Accessory Box</b>		
9662432004E	Handle set	1
	Screws/nuts and rubber for motherboard and devices	one bag
2002432004	User manual	1

## Optional Accessories

Part Number	Description
IPC-DT-3120E	Mobile rack for converting a 3.5" drive bay to dual 2.5" SATA HDD trays
IPC-DT-5230E	Mobile rack for converting dual 5.25" drive bays to three 3.5" SATA HDD trays
1700007351	M Cable SATA 7P/SATA 7P 40CM C=R 90/180 SATA data cable, 180 degree right angle, 40cm
1700029268-01	Power cable for GPU card (Two 4-pin 12V connectors to one 6+2 pins PCIe power connector)
1700024754-01	Power cable for GPU card (Two B4P Molex connectors to one 6+2 pins PCIe power connector)

\* When choosing ASMB-7 series for system motherboard, 2pcs right-angle SATA cable (PN: 1700007351) are necessary for hot-swap driver bay.

\* If GPU card with 2 power connectors, please use 1700029268-01\*1 + 1700024754-01\*1; If GPU card with 1 power connector, please use 1700029268-01.

\* Only 500W or higher wattage PSU support 1700029268-01 and 1700024754-01 for high-end GPU card.

## Power Supply Options

(For detailed power supply specs, please refer to Chapter 13)

Part Number	80 Plus Grade	Wattage	Type	Input
PS8-300ATX-ZBE	Bronze	300W	Single	AC 100 ~ 240 V (full range)
PS8-500ATX-BB	Bronze	500W	Single	AC 100 ~ 240 V (full range)
PS8-700ATX-BB	Bronze	700W	Single	AC 100 ~ 240 V (full range)
RPS8-500ATX-GB	Gold	500W	1+1 Redundant	AC 100 ~ 240 V (full range)