

Hyper SuperServer SYS-121H-TNR



More details here

Key Applications



Virtualization, Software-defined Storage, AI Inference and Machine Learning, Cloud Computing, Enterprise Server,

Key Features

- Dual Socket E (LGA-4677) 4th Gen Intel® Xeon® Scalable processors;
- 32 DIMM slots supporting up to 8TB of memory; RDIMMs up to DDR5-4800;
- 3 PCIe 5.0 x16 slots with support for GPU/Accelerator cards;
- Flexible networking options with 1 AIOM networking slot (OCP NIC 3.0 compatible);
- 8x 2.5" hot-swap NVMe/SATA/SAS drive bays; Optional 4x 2.5" hot-swap NVMe/SATA/SATA drive bays; 2x internal M.2 NVMe/SATA drive slots; Optional RAID support via storage add-on card;
- 8 heavy duty hot-swap fans with optimal fan speed control;



Form Factor	1U Rackmount Enclosure: 437 x 43 x 747mm (17.2" x 1.7" x 29.4") Package: 605 x 206 x 1032mm (23.8" x 8.1" x 40.6")
Processor	4th Gen Intel® Xeon® Scalable processors Dual Socket LGA-4677 (Socket E) supported 4 UPI Intel Xeon CPU Max Series with high bandwidth memory (HBM) (Supports up to 350W TDP CPUs (Aircooled), Supports up to 350W TDP CPUs (Liquid Cooled), CPUs (air cooled) with TDP over 250W are only supported under specific conditions. Contact customer support for details.)
System Memory	32 DIMM slots Up to 8TB ECC RDIMM, DDR5-4800MHz
Drive Bays	8x 2.5" hot-swap NVMe/SATA/SAS drive bays; Optional RAID support via RAID Controller AOC
Expansion Slots	1 PCIe 5.0 x16 FH, 6.6"L slot(s) 2 PCIe 5.0 x16 FH, 10.5"L slot(s)
On-Board Devices	Chipset: Intel® C741 Network Connectivity: 2x 1GbE BaseT with Intel® i350-AM2 (optional) 4x 1GbE BaseT or 4x 1GbE SFP with Intel® i350-AM4 (optional) 2x 10GbE BaseT with Intel® X550-AT2 (optional) 2x 10GbE SFP+ with Intel® X710-BM2 (optional) 4x 10GbE SFP+ with Intel® XL710-BM1 (optional) 4x 10GbE RJ45/SFP+ with Intel® X710-TM4 (optional) 2x 25GbE SFP28 with Broadcom® BCM57414 (optional) 4x 25GbE RJ45/SFP28 with Mellanox® CX-4 Lx EN Intel® X550-AT2 (optional) 2x 100GbE QSFP28 with Broadcom® BCM57508 (optional) IPMI: Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Input / Output	LAN: 1 RJ45 Dedicated BMC LAN port USB: 2 USB 2.0 port(s) (2 rear) 1 USB 3.0 port(s) (1 front) Video: 1 VGA port(s)



System Cooling	8x 4cm heavy duty fan(s) Liquid Cooling: Direct to Chip (D2C) Cold Plate (optional)
Power Supply	1U 800W/1200W Redundant Titanium CRPS w/PMBus power supply Dimension (W x H x L): 73.5 x 40 x 265 mm Output Type: 25 Pairs Gold Finger Connector
System BIOS	BIOS Type: AMI 256MB SPI Flash
Management	SuperDoctor® 5; Watch Dog; NMI; SUM; KVM with dedicated LAN; SPM; Intel® Node Manager; SSM; IPMI 2.0; Redfish API
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Height: 1.7" (43 mm) Width: 17.2" (437 mm) Depth: 29.4" (747 mm) Gross Weight: 49 lbs (22.2 kg) Net Weight: 34 lbs (15.4 kg) Packaging: 8.1" (H) x 23.8" (W) x 40.6" (D) Available Color: N/A
Operating Environment	Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	Super X13DEM
Chassis	CSE-HS119-R1K24P2