


# SPCIE-C236

Full-size PICMG 1.3 CPU Card supports LGA 1151 Intel® Xeon® E3, Core™ i3/Pentium®/Celeron® CPU per Intel® C236, ECC & non-ECC DDR4, VGA/iDP, Dual Intel® PCIe GbE, mSATA, PCIe Mini, USB 3.2 Gen 1 (5Gb/s), SATA 6Gb/s, HD Audio, Intel® AMT, iRIS-2400 and RoHS



## PCIe Mini & mSATA colay



PCIe Mini interface provides SATA, PCIe x1 and USB signals to support full-size or half-size devices, such as mSATA, PCIe devices, and wireless LAN cards.

## Specifications

- ◆ CPU  
LGA 1151 socket supports Intel® Xeon® E3 v5/v6, 6th/7th generation Core™ i3, Pentium® or Celeron® processor
- ◆ Chipset  
Intel® C236
- ◆ Memory  
Four 288-pin 1866/2133 MHz dual-channel ECC & non-ECC unbuffered DDR4 DIMMs support up to 64GB
- ◆ BIOS  
UEFI BIOS
- ◆ Graphics Engine  
Intel® HD Graphics Gen 9 supports DX11/12, OpenCL 2.x and OpenGL 4.3/4.4 Decode/Encode for HEVC, VP8, VP9, VDENC
- ◆ Display Output  
Dual independent display  
1 x VGA (up to 1920x1200@60 Hz)  
1 x iDP interface for HDMI, LVDS, VGA, DVI and DisplayPort (up to 3840x2160@60 Hz)
- ◆ Ethernet  
LAN1: Intel® I219LM Clarkville-V with Intel® AMT 11.0 supported  
LAN2: Intel® I210 PCIe controller
- ◆ External I/O Interface  
2 x USB 3.2 Gen 1 (5Gb/s)
- ◆ Internal I/O Interface  
1 x KB/MS (1x6 pin) 2 x RS-232/422/485 (2x5 pin, P=2.54)  
1 x LPT (2x13 pin) 2 x USB 3.2 Gen 1 (5Gb/s) (2x10 pin)  
1 x mSATA (SATA & USB signal) 6 x SATA 6Gb/s (RAID 0/1/5/10 supported)  
1 x USB 2.0 (180° Type-A) 6 x USB 2.0 (2x4 pin, P=2.54)  
2 x RS-232 (2x5pin, P=2.54)
- ◆ Front Panel  
1 x Front Panel (1x10 pin, power LED, HDD LED, speaker, power button, reset button)
- ◆ LAN LED  
2 x LAN LED (1x2 pin)
- ◆ Audio  
Support 7.1 channel HD Audio by IEI AC-KIT-888S-R10 kit
- ◆ TPM  
1 x TPM (2x10 pin)
- ◆ SMBus  
1 x SMBus (1x4 pin)
- ◆ I²C  
1 x I²C (1x4 pin)
- ◆ iRIS Remote Management Module  
1 x iRIS-2400 slot (optional)
- ◆ Expansion  
**16-lane PCIe link from CPU via golden finger:**  
Supports one PCIe x16, or two PCIe x8, or one PCIe x8 + two PCIe x4 on the backplane (configured via BIOS)  
**4-lane PCIe link from PCH via golden finger:**  
Supports four PCIe x1 slots or one PCIe x4 slot on the backplane (configured via BIOS switch)  
**1 x Full/Half-size PCIe Mini card slot (supports mSATA)**
- ◆ Watchdog Timer: Software programmable, supports 1~255 sec. system reset
- ◆ Digital I/O: 8-bit digital I/O (2x5 pin)
- ◆ Fan Connector  
1 x CPU smart fan (1x4 pin)  
1 x System smart fan (1x3 pin)
- ◆ Power Supply  
5V/12V, AT/ATX support
- ◆ Power Consumption  
5V@3.22A, 12V@6.81A, 3.3V@1.21A, 5VSB@0.18A (Intel® Xeon® E3-1275 v5 3.60 GHz CPU with 64GB (16GBx4) 2133 MHz DDR4 memory)
- ◆ Operating Temperature  
-20°C ~ 60°C
- ◆ Operating Humidity  
5% ~ 95%, non-condensing
- ◆ Dimensions  
338 mm x 126 mm
- ◆ Weight  
GW: 1000g / NW: 420g
- ◆ CE/FCC compliant



## Features

- PICMG 1.3 full-size CPU Card
- LGA 1151 Intel® Xeon® E3 v5/v6, 6th/7th generation Core™ i3, Pentium® or Celeron® processor supported
- Four 288-pin 1866/2133MHz DDR4 ECC & non-ECC unbuffered DIMM
- Supports dual independent display by VGA & internal DP pin header
- Supports PCIe Mini device & mSATA via PCIe Mini card slot
- Intel® PCIe GbE with Intel® AMT 11.0 supported
- Supports RAID 0, 1, 5, 10 function via SATA 6Gb/s
- TPM 1.2 & 2.0 hardware security function supported by TPM module

## Packing List

1 x SPCIE-C236 single board computer	1 x Mini jumper pack
1 x SATA cable	1 x QIG

## Ordering Information

Part No.	Description
SPCIE-C236-R10	Full-size PICMG 1.3 CPU Card supports LGA 1151 Intel® Xeon® E3, Core™ i3/Pentium®/Celeron® CPU per Intel® C236, ECC & non-ECC DDR4, Dual Intel® PCIe GbE, VGA/iDP, USB 3.2 Gen 1 (5Gb/s), SATA 6Gb/s, PCIe Mini, HD Audio, Intel® AMT, and RoHS
SPCIE-C236-i2-R10**	Full-size PICMG 1.3 CPU Card supports LGA 1151 Intel® Xeon® E3, Core™ i3/Pentium®/Celeron® CPU per Intel® C236, ECC & non-ECC DDR4, Dual Intel® PCIe GbE, VGA/iDP, VGA/iDP, USB 3.2 Gen 1 (5Gb/s), SATA 6Gb/s, PCIe Mini, HD Audio, Intel® AMT, iRIS-2400 and RoHS
19800-000049-RS	LPT flat cable, 240mm, P=2.54
19800-000075-RS	PS/2 KB/MS cable with bracket, 220mm, P=2.0
19800-003100-300-RS	Dual port USB 2.0 cable with bracket, 300mm, P=2.54
19800-010500-200-RS	USB 3.2 Gen 1 (5Gb/s) cable with bracket, 450mm
32102-000100-200-RS	SATA power cable, MOLEX 5264-4P to SATA15P
32205-000702-100-RS	RS-232 cable, 230mm, P=2.54
32205-003800-300-RS	RS-422/485 cable, 200mm, P=2.0
AC-KIT-892HD-R10	7.1 channel HD Audio kit with Realtek ALC892 support dual audio streams
CF-1150SA-R10	Special cooler kit for LGA1150, high-performance compatible, 95W
CF-1150SB-R11	Special cooler kit for LGA1150, high-performance compatible, 65W
CF-1150SC-R20	Special cooler kit for LGA1150, 1U chassis compatible, 65W
CF-1150SE-R11	Special cooler kit for LGA1150, high-performance compatible, 95W
CF-1150SF-R10	Special cooler kit for LGA1150, 1U chassis compatible, 54W
DP-DP-R10	DisplayPort to DisplayPort converter board (for IEI iDP connector)
DP-DVI-R10	DisplayPort to DVI-D converter board (for IEI iDP connector)
DP-HDMI-R10	DisplayPort to HDMI converter board (for IEI iDP connector)
DP-LVDS-R10	DisplayPort to LVDS converter board (for IEI iDP connector)
DP-VGA-R10	DisplayPort to VGA converter board (for IEI iDP connector)
SAIDE-KIT01-R10	SATA to IDE/CF converter board

\*\*By order production, MOQ: 100